NEXT GENERATION 500KV HVDC EXTRUDED CABLE SYSTEM

Hideo Tanaka

Yukihiro Yagi

VISCAS Corporation

(From 1. Oct., Furukawa Electric)







Future expectation in the field of HVDC extruded cable system

- Clear trend of increased installation of renewable generation.
- Also the case in Japan, where still limited amount of renewable generation.
- Japanese government now encouraging to expand renewable generation.
- → National project has commenced to develop off shore wind farm with 500kV HVDC mass power transportation.

Future expectation in the field of HVDC extruded cable system

- Clear trend of increased installation of renewable generation.
- Also the case in Japan, where still limited amount of renewable generation.
- Japanese government now encouraging to expand renewable generation.
- → National project has commenced to develop off shore wind farm with 500kV HVDC mass power transportation.
- Increased demand for higher voltage HVDC extruded cable expected in the very near future.
- Improved productivity of HVDC extruded cable as well as raw material to be achieved to cope with above future trend.

Newly developing next generation HVDC extruded cable system

- Development project (up to 500kV level) is on going.
- HVDC performance (space charge, resistivity, etc.) improved by material modification.

Aim




DC 320kV 1x2500mm²



DC 500kV 1x1800mm²

Basic property of the next generation system

• Test results on model (flat sheets / model cables).



Space charge behavior Outer semi-con Inner semi-con layer layer 480h Charge Density [C/m³] 0 Position [mm]

Result on model cable

Results on flat sheet specimens

System development (1)

- 320kV underground system PQ test successfully completed.
 - ✓ Accordance with TB496 (LCC)
 - \checkmark 2500mm²(Cu), U_o=320kV, T_{cond} = 90 deg.C
 - ✓ Outdoor terminations (Porcelain, Composite)
 - ✓Intermediate joints (Pre fabricated type, Premolded type)





System development (2)

- 320kV submarine system PQ test just started.
 - ✓ Accordance with TB496 (LCC).
 - \checkmark 2500mm²(Cu), U_o=320kV, T_{cond} = 90 deg.C.
 - ✓ Mechanical tests had been performed on cable and factory

joint.

✓ Repair Joint included.



✓ 500kV submarine system development under preparation.

Thank you for your attention!