Jicable HVDC'16 Workshop Topic 4

Submarine HVDC Links

Christian Rémy – Prysmian PowerLink




Submarine HVAC and HVDC cables




Submarine cables could make use of different technologies, depending on specific choices of system operators. In general:

- Long connections make use of DC transmission
- Large powers require high voltages
- Long HVAC connections suffer power de-rating vs. length

Submarine power cable projects worldwide



GLOBAL EXPERIENCE – HV SUBMARINE CABLE SYSTEMS Prysmian Group



Submarine HVDC Cable Technologies



ΥI	D	F
Л		ᆮ

■±600 kV

■3000 MW

VSC any voltage LCC up to 250 kV

P-Laser

■±525 kV

■2700 MW

■Both LCC and VSC

MI paper

■±525 kV

■2400 MW

■Both LCC and VSC

MI-PPL

■±700 kV

■3400 MW

■Both LCC and VSC

wont: Submarine cables may have different armouring design mainly depending on water depth NOTE 2: Rating depends on ambient and installation parameters | Icable HVDC'16 |

WORKSHOP

The Western Link HVDC Project


Main features

- ✓ Largest Cable Contract ever awarded
- ✓ Highest Voltage DC System ever (600 kV with PPL insulation)
- ✓ Highest Power of any long length DC system (2250 MW continuous, 2400 MW 6 hour overload)
- ✓ Overall route length approx. 422 km (37 km underground, 385 km submarine)



SA.PE.I (Sardinia-Peninsula Italiana) PROJECT MAIN FEATURES

RATED POWER 1000 MW (bipolar configuration, 2x500MW) ◆ RATED VOLTAGE 500 kV DC ♦ ROUTE LENGTHS: 2x425 km - Submarine 2x15 km - Land ♦ MAX WATER DEPTH 1650 m ◆ CABLE TYPE AND SIZE Paper, MI ♦ POLE 1 IN SERVICE SINCE Dec 2008 ♦ POLE 2 IN SERVICE SINCE Oct 2010 Fiume Santo Nettuno




Jicable HVDC'16 WORKSHOP



North Sea Link HVDC Interconnector 1400MW

Main features


- ✓ At 740Km it is the longest ever HVDC Link with subsea / land cables
- ✓ Prysmian has been awarded Lot 2 and Lot 3, route length 2 x 470Km
- ✓ Proven Prysmian mass impregnated paper cable, nominal DC voltage ±515 kV
- √ 2.5Km land cables to the UK converter station, converter is based on VSC




North Sea Link



TRANS BAY HVDC CABLE PROJECT - San Francisco bay



German HVDC Projects - Prysmian



HVDC Submarine & Land Connections in the German North Sea

Project	Voltage (kV)	Power
BorWin2	300 kV	800 MW
HelWin1	320 kV	864 MW
HelWin2	250 kV	576 MW
SylWin1	320 kV	690 MW
BorWin3	320 kV	900 MW
DolWin3	320 kV	900 MW

Approx. 2000 km HVDC cable, ~ 650 km of which are land cables, with more than 900 joints




COBRAcable HVDC interconnection









Main features

- ✓ Submarine section
 - route length 310 km
 - max. burial depth 13 m
 - max. water depth 50 m
 - minimum burial depth requirement (2K criteria)
- ✓ Land section
 - route length 21 km
 - max. burial depth 1,3 m







Land Systems



INELFE 320 kV DC Spain-France Interconnection







Main features

2000 MW Power Rating

65 km route length

Longitudinally Welded Aluminum Sheath (WAS)

320 kV XLPE cable with 2500 mm² Cu conductor

Long lengths (Up to 2190 m)





320 kV DC France-Italy Interconnection





Main features

Nominal voltage: ±320 kVdc

Rated power: 2x600 MW (two bipoles, 4 cables)

Al conductor 2500 mm2 with extruded insulation

190 km fully underground

Under construction





Thank You for Your Attention!

